Data Sheet

AEGEX100M™

Intrinsically Safe Tablet



Supplied by

247cble.com



Aegex100M™ Intrinsically Safe Tablet

Aegex Technologies is proud to offer its 2nd Generation intrinsically safe tablet, the Aegex100M with faster wireless services, enhanced memory, and expanded storage. Operating in the most hazardous industries with explosive environments, Aegex solutions bring real-time connectivity to help organizations harness the power of data to optimize efficiency.













CHEMICAL BIOFUEL

PHARMACEUTICAL

PAINTS & SPECIALTY COATINGS

FOOD & BEVERAGE

The Aegex100M[™] Intrinsically Safe Tablet is positioned to be the most advanced, efficient, and rugged Windows tablet, with pending Zone 0 / Division 1 certification in hazardous areas. Simple to deploy, it is the basis for an Industrial Internet of Things platform for hazardous industries, allowing operations to easily begin their digital transformation to Industry 4.0

Purpose-Built Intrinsically Safe

Designed from the ground up to be the lightest and fastest Windows device in its class, the Aegex100M is currently pending certification for ATEX/IECEx Zone 0 and UL 913 Class I, II, III, Division 1.

Hazardous Area Mobility

At the center of hazardous area mobility, the Aegex100M supports all of your operational needs including: Maintenance, Inspections, Workflow Management, Automation & Process Control, MES, Diagnostics & Calibration, HMI, Asset Management and many more.

Enterprise Class Solutions

Safely and securely connect your hazardous area operations and allow your teams to share mission-critical data across the entire organization; enabling greater visibility, collaboration, decision making, and performance.



Pending Certification for: ATEX / IECEx Zone 0 UL913 C I, II, III Div 1



- 10.1" AHVA Display
- Powered by Intel Quad-Core
- Apollo Lake Processor
- 8GB RAM











Specifications

| Pend Certification | In certification for Zone 1 & Zone 0 certification according to ATEX, IECEx, and UL 913 standards. | |
|-----------------------------|---|---|
| | UL 913 8th Edition, CSA C22.2 No. 60079-0 & -11 Class I, II, III, Division 1, Groups A-G, T4 Tamb = -20°C+50°C, IP67 IECEX Ex ia IIC T4 Ga Ex ia IIIC T135°C Da Tamb = -20°C+55°C, IP67 | ATEX II 2G Ex ia IIC T4 Ga Ex ia IIIC T135°C Da Tamb = -20°C+55°C, IP67 |
| Exterior | W x H x D: 278 x 207 x 13.8 mm (10.94 x 8.15 x 0.54 in) – without battery W x H x D: 278 x 207 x 28.3 mm (10.94 x 8.15 x 1.11 in) – at battery section Estimated final weight: 1430g (3.08 lbs) | |
| Display | 10.1" / 25.6 cm AHVA display. WQXGA (2560 x 1600 px). Contrast 1000:1 (min.: 800:1). Brightness 540 NITs. Viewing angle (up/down, left/right) 170°. 16.7M colours | |
| Battery | 7.2V 2 x 3420mAh, 49.68Wh. Rechargeable Lithium Ion | |
| Charging Time. (In standby) | Wall adaptor: 0-90% in 2.5hours, to 100% in approx. 3.5 hours Docking station: 0-90% in 2.5hours, to 100% in approx. 4 hours | |
| CPU & Storage | Intel® Quad-Core Apollo Lake processor. Base: 1.6GHz, Burst 1.8GHz. 8GB RAM, 256GB storage MicroSDXC Card Slot (up to 2 TB cards supported) | |
| Wireless & LTE | Wi-Fi 802.11 a/b/g/n/ac/. Bluetooth 5.2 + HS. NFC. LTE Optional: Worldwide LTE-A Cat 12 and UMTS/ HSPA+ | |
| Location | GPS / GLONASS / Galileo. (Cold start < 30s, Hot start < 2s) | |
| Connections | Magnetic pin connector for rapid charging with Aegex Wall Charger Docking connector supports LAN, USB 2.0, 3.0, USB-C, HDMI, SD Card, and audio jack | |
| Software | Windows 11 IoT. AegexScan™ Barcode Scanning Application – Optional | |
| Video & Audio | Main Camera (rear-facing): 8MP Auto-focus with flash Image: 3264 x 2448 px jpg, video: 1080p (Full HD 1920 x 1080) 30 fps Secondary Camera (Front-facing) Image: 1920 x 1080 px jpg, video: 1080p (FullHD 1920x1080) 30 fps 1 digital microphone front facing microphone array. Stereo speakers | |
| Sensors | Ambient light sensor (ALS), Accelerometer, Gyroscope, E-Compass, SAR proximity sensor | |
| Security | Intel® TXE Boot Guard 2.0 FW TPM (Intel® PTT3) Intel® Trusted Execution Engine Interface (Intel® TXEI) Driver Intel AES New Instructions BitLocker | |
| In the Box | Aegex100M™ Intrinsically Safe Tablet Tablet Charger: 12VDC 3.33A power supply and adaptor | |

Have a particular application in mind? We'd welcome a call on +44 (0) 1189 169 420

For your info, ABLE are the premier direct partner for Aegex within the UK and can assist you and your customers in the following areas:

- Pre-loading of any free issue industry standard software on to the tablet
- Handle future pre-arranged 'call off' quantities for expedient delivery
- Offer after sales support utilising our in-house Windows certified expertise
- Offer training via our state-of the art training rig into how the Aegex tablet can be used

ABLE can offer bespoke asset management software development based on your your requirements. ABLE could offer this in a two week turnaround once your requirements have been fully understood. For more information, email us now at info@247able.com

Did you know? The Aegex tablet can become an engineer service tool during annual service & calibrations, meaning the engineer does not require to connect his own laptop to any platform system. All reporting data postservice can be emailed to ABLE's factory trained service team from the tablet, along with any relevant photos taken with the tablet.

Download ABLE Remote Support Brochure





