Data Sheet

ISAFE MOBILE

IS440.1



Supplied by

247cble.com

Call us on +44 (0)118 916 9420 | Email info@247able.com



DATASHEET





APPROVALS



ATEX approval: EX-Zone 1/21 requested
Il 2G Ex ib IIC T4 Gb
Il 2D Ex ib IIIC T135°C Db

NEC500 approval: requested Class I, II, III Division 1 Groups A B C D E F G T4



TECHNICAL FEATURES MODEL M440A01

Operating system	ISM-OS
Processor	Qualcomm® QCM6490 Octa Core
Memory	4 GB RAM 64 GB internal memory
Supported frequency bands	4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI/13/14/17/20/25/26/28/29/30/66/68/71 4G LTE-TDD: B38/39/40/41/42/43/48 5G NR: n1/n2/n3/n5/n7/n8/n12/n14/n20/n25/n28/n30/n38/n40/n41/n48/n66/n71/n77/n78/n79
Dimensions	Size: 136,6 x 71,5 x 32 mm weight: 322 g
Display	2,4" Corning® Gorilla® Glass 3 rd generation 240 x 320 pixels
Battery	2400 mAh (4800 mAh optional) replaceable
Camera	8 MP AF front camera
SIM support	1 nano SIM + eSIM
Connections	Wi-Fi® 6: IEEE 802.11 a/b/g/n/ac/ax/e/k/r/v Bluetooth® 5.2 GPS, A-GPS, Glonass, A-Glonass, Beidou, Galileo Near Field Communication (NFC)
Interfaces	8-pin ISM interface for optional audio accessories
Sensors	Accelerometer, Gyroscope, Magnetic, Pressure sensors
Types of protection	IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +55 °C

FURTHER FEATURES

Red key top | Optional functions assignable via Button App (system integrated), e.g. LWP

Side key left | Optional functions assignable via Button App (system integrated), e.g. PTT

Channel selector knob (top)

Function key: M1 & M2 assignable via Button App

Amplified loudspeaker

Charging contacts for Desktop Charger

Integrated Belt clip

SET CONTENT

5G Radio, Battery, i.safe PROTECTOR 2.0 Type C USB Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Belt clip, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.