## **Data Sheet**

# **ISAFE MOBILE**

IS930.1



Supplied by

247cble.com

Call us on +44 (0)118 916 9420 | Email info@247able.com





The robust and powerful tablet of the Industry 4.0 generation is Android Enterprise Recommended and, thanks to its zero-touch functionality, can be used quickly and is ideally suited for maintenance applications in the IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap and a separate leather bag with a shoulder/belt or carry strap system are further highlights.

Android is a trademark of Google LLC. All trademarks and copyrights are the properties of their respective owners. © 2023 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1030MD01REV15\_EN\_09.2023







ATEX approval: EX-Zone 1/21 Il 2G Ex ib IIC T4 Gb Il 2D Ex ib IIIC T135°C Db IP6X



IECEx approval: EX-Zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X



NEC500 approval: Class I, II, III Division 1 Groups A B C D E F G T4



EAC approval: 1Ex ib IIC T4 Gb X Ex ib IIIC T135°C Db X IP64

Further approvals: INMETRO (Brazil) | KCs (South Korea) | PCEC (China) | JNIOSH (Japan) | SANS (South Africa)

### **TECHNICAL FEATURES**

Operating system	Android <sup>™</sup> 10   Upgrade to Android <sup>™</sup> 13 (available Q3/2023)
Processor	SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)
Memory	4 GB RAM $\mid$ 64 GB internal memory $\mid$ microSD memory up to 512 GB
Frequencies	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39
Dimensions	size: 237 x 156 x 22 mm   weight: 890 g
Display	8" Gorilla Glass® 3. generation   1200 x 1920 pixels
Battery	8400 mAh
Camera	13 MP AF rear camera   5 MP FF front camera
Connections	WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot Bluetooth* 5 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication
Types of protection	IP68 dust-/waterproof   MIL-STD-810H   usable from -20 °C to +60 °C

#### **FURTHER FEATURES**



SOS key for loneworker protection LWP ready (third party application required, based on country specific regulations)



2 freely programmable keys



Usable with gloves



Accelerometer, gyroscope, magnetic, temperature and humidity, proximity sensors



Magnetic charger port

#### **SET CONTENT**

Tablet with integrated battery, Hand Strap, i.safe PROTECTOR 2.0 Type C USB Cable, i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Power Adapter universal, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.