

Quick Selection Guide for Mid-West Products

| MODEL NUMBER <small>Click on product number to view full specifications and datasheet online</small> | SENSOR TYPE | MINIMUM RANGE | MAXIMUM RANGE | ACCURACY % FULL SCALE | MAXIMUM TEMP. (F) | MWP (PSIG) |
|---|--------------------------|---------------|---------------|--------------------------------|-------------------|----------------|
| 105 | Bellows | 0-10" H2O | 0-79.9" H2O | ±1/2% or 1% | 200°F | 500 to 6,000 |
| 106 | Bellows | 0-80" H2O | 0-800" H2O | ±1/2% or 1% | 200°F | 500 to 6,000 |
| 109 | Bourdon Tube | 0-15 PSID | 0-6000 PSID | ±1/2% or 1% | 200°F | 500 to 6,000 |
| 114 | Diaphragm | 0-20" H2O | 0-600" H2O | ±2% | 200°F | 1,500 or 3,000 |
| 115 | Bellows | 0-10" H2O | 0-69.9" H2O | ±1% | 200°F | 500 or 1,000 |
| 116 | Bellows | 0-70" H2O | 0-800" H2O | ±1% | 200°F | 500 or 1,000 |
| 120 | Piston | 0-5 PSID | 0-110 PSID | ±2% | 200°F | 3,000 to 6,000 |
| 121 | Piston | 0-5 PSID | 0-110 PSID | ±2% | 200°F | 3,000 to 6,000 |
| 122 | Piston | 0-5 PSID | 0-110 PSID | ±5% | 200°F | 3,000 |
| 123 | Piston | 0-150 PSID | 0-400 PSID | ±2% | 200°F | 3,000 to 5,000 |
| 124 | Piston | 0-5 PSID | 0-400 PSID | ±2% | 200°F | 10,000 |
| 130 | Diaphragm | 0-5" H2O | 0-400" H2O | ±5% or 3/2/3% (Based on range) | 200°F | 300 or 500 |
| 140 | Diaphragm | 0-50" H2O | 0-100 PSID | ±5% or 3/2/3% (Based on Range) | 200°F | 1,500 or 3,000 |
| 142 | Diaphragm | 0-20" H2O | 0-25 PSID | ±3/2/3% | 200°F | 1,500 or 3,000 |
| 522 | Diaphragm | 0-5 PSID | 0-50 PSID | ±5% | 200°F | 1,000 |
| 522A | Diaphragm (3-Color Dial) | 0-5 PSID | 0-50 PSID | ±5% | 200°F | 1,000 |
| 555A | Diaphragm | 0-2.0 PSID | 0-43 PSID | ±5% | 200°F | 300 |
| 700 | 316L SS Diaphragm | 0-5 PSID | 0-300 PSID | ±0.50% | 175°F | See Bulletin |
| HAZARDOUS LOCATION SWITCHES | | | | | | |
| 220 | Piston | 0-5 PSID | 0-100 PSID | ±3/2/3% | 200°F | 4,000 |
| 240 | Diaphragm | 0-20" H2O | 0-100 PSID | ±3/2/3% | 200°F | 1,500 |
| O. E. M GAUGES | | | | | | |
| 126 | Piston | 0-5 PSID | 0-20 PSID | ±5% | 200°F | 3,000 |
| 127 | Piston | 0-25 PSID | 0-100 PSID | ±5% | 200°F | 3,000 |
| 146 | Diaphragm | 0-50" H2O | 0-30 PSID | ±5% | 200°F | 1,000 |
| 444 | Slider Indicator | 0-5 PSID | 0-25 PSID | ±5% | 200°F | 300 |
| 555 | Diaphragm | 0-2.0 PSID | 0-50 PSID | ±5% | 200°F | 300 |
| 522 | Diaphragm | 0-5 PSID | 0-50 PSID | ±5% | 200°F | 1,000 |

FLOW INSTRUMENTATION

Model 300 Delta Tube
Series 800 Flow Test Kits

ACCESSORIES

Three & Five Valve S.S. Differential Pressure Manifolds
Basic Snubber – Non-Adjustable (Available in Brass and Stainless Steel)
Model 150 Adjustable Pulsation Dampener (Available in Brass and Stainless Steel)
Model 200 Pressure Limiting Valve (Available in Aluminum, Brass and Stainless Steel)
Diaphragm / Chemical Seals

Registered Address

ABLE Instruments & Controls Ltd
Cutbush Park, Danehill, Lower Earley,
Reading, Berkshire, RG6 4UT. UK.

Phone

+44 (0)118 9311188

Email

info@able.co.uk

Web

able.co.uk

E-commerce

247able.com



Registered in England No. 01851002. VAT No. GB 417 2481 61